

OmniLink® TM-T88V-i Intelligent Printer



Intelligent Printer
POS

An intelligent top-load printer for mobile POS, cloud services and peripherals.

Industry-leading top-load POS printer with retail-hardened PC — open-platform mobility for mobile POS deployments, cloud-based services, online ordering and more

Peripheral support — 4 USB ports and 1 Serial port or VGA for connecting up to 5 devices; easy control of peripherals through ePOS™ device control

Compatible — supports handheld scanners, scales, 2" x 20" customer displays, wedge magnetic stripe readers and more

Versatile — Ethernet and optional wireless; supports Web-based printing from virtually any smartphone and tablet

Easy implementation — adds cloud services without the need for legacy POS integration

Fast — prints up to 300 mm/sec, supports a 3" media width

Paper-saving options — reduce your paper usage by up to 30 percent

Comprehensive service and support — dedicated technical resource team and customized solutions; 3-year limited warranty

Printing

Print Method Thermal line printing
Print Speed 11.8"/sec (300 mm) max. for graphics and text,
 2.4"/sec for ladder and 2D barcodes

Fonts
 Font A (default): 12 x 24
 Font B: 9 x 17 (including 2-dot horizontal spacing)

Column Capacity
 80 mm: 42/56 columns
 58 mm model: 30/40 columns

Character Size (W x H mm)
 Font A: 1.41 x 3.39
 Font B: 0.99 x 2.40

Character Set 95 Alphanumeric, 18 International,
 128 x 43 Graphic (including user-defined page), Traditional/
 Simple Chinese, Thai, Japanese, Korean

Barcode UPC-A/E, CODE 39/93/128, EAN8/13, ITF, CODABAR
 2D symbols: PDF417, QR-CODE, MaxiCode, Composite
 Symbology, GS1-128, GS1 DataBar, Omnidirectional/Truncated/
 Limited/Expanded

Media Handling

Media Dimensions
 80 mm: 3.13" ± 0.02" (width) x 3.27" (roll diameter)
 (79.5 ± 0.5 x 83 mm)

58 mm: 2.26" ± 0.02" (width) x 3.27" (roll diameter)
 (57.5 ± 0.5 x 83 mm)

Thickness 55 – 80 µm

Retail-hardened PC

Processor Intel® Atom™ ARM9 Processor (400 MHz)

System Memory 256MB

Operating System Embedded Linux®

Interface

USB 2.0 x 4
 100 Base-TX / 10 Base-T
 Ethernet-compliant interface
 VGA x 1 (D-sub 15-pin female)

General

Interfaces
 Ethernet interface (100 Base-TX / 10 Base-T)
 USB 2.0 Type A (4x)
 USB 2.0 Micro-AB
 VGA x 1 (D-sub 15-pin female)

Reliability
 MTBF: 360,000 hours
 MCBF: 70,000,000 lines
 Auto Cutter: 2 million cuts

Data Buffer
 Receive: 45 bytes or 4KB, selectable
 User-defined: 12KB

Macro: 2KB
 NV graphics: 256KB
 NV user: 1KB

Page mode area: 106K
D.K.D. Function 2 drivers

Power Consumption Approx. 1.8 A (mean)

Power 24 Volts DC ± 7%

Options Auto cutter, Near-end sensor

Dimensions 5.71" x 7.68" x 5.83" (145 x 195 x 148 mm)
 (W x D x H)

Weight 3.5 lb (1.6 kg)

Color Epson Dark Gray (EDG), Epson Cool White (ECW)

Server Systems HTTP server (Apache)

On board Intelligence

Intelligent Software WebPOS Configuration, ePOS-Device
 Drivers and setup utility are available on CD or at
 pos.epson.com

Standards and Approvals
 EMI standards: FCC/ICES-003 Class A

Safety standards: UL1950/GSA C22.2 No. 950

Warranty 3-year limited warranty in the U.S. and Canada

What's in the Box


OmniLink TM-T88V-i printer, User manual (CD), Power switch
 cover, Paper roll, Adapter C with AC cord, Start Here poster

Eco Features

RoHS compliant
 Recyclable product¹
 Epson America, Inc. is a SmartWay® Transport Partner²

Ordering Information

Omnilink TM-T88V-i C31CA85790



¹ For convenient and reasonable recycling options, visit www.epson.com/recycle | ² SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness

Better Products for a Better Future™
eco.epson.com



Epson America, Inc.
 3840 Kilroy Airport Way, Long Beach, CA 90806

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON is a registered trademark, EPSON Exceed Your Vision is a registered trademark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. OmniLink is a registered trademark and ePOS is a trademark of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2016 Epson America, Inc. Com-SS-Oct-13 CPD-52077 7/16