

## Mobile Printers

## 2" Receipt/Label Printer

The LK-P12 is a powerful mobile printer in a small, easy to carry package. Designed for both receipt and label the printing, the LK-P12 works in multiple use cases. With Wi-Fi and Bluetooth options, plus support for most standard mobile printers, the LK-P12 is easy to integrate into any existing mobile printing application.



### COMPATIBILITY

Built in USB, serial, Bluetooth or Wi-Fi, plus support for ESC/POS and ZPL commands, it's the perfect solution for any application



### FAST PRINTING

Printing speeds of 5"/sec mean you're never left waiting for a receipt to finish printing



### EASY PAPER LOADING

Easy drop-in thermal paper loading won't slow you down on the go



### BUILT FOR LABELS

Gap and black mark sensors, along with an optional label peeler, make the LK-P12 an ideal mobile label printer



# Mobile Printers

## 2" Receipt/Label Printer

PART NUMBER	LK-P12-NSB	LK-P12-NSW	LK-P12-PSB	LK-P12-PSW
Label Peeler	No	No	Yes	Yes
Interface	USB/Serial/Bluetooth 4.2	USB/Serial/Wi-Fi (802.11 a/b/g/n)	USB/Serial/Bluetooth 4.2	USB/Serial/Wi-Fi (802.11 a/b/g/n)
Emulation	ESC/POS, CPCL, ZPL and EPL Command compatible			
Print Method	Direct Thermal			
Printing Speed	5"/sec (127mm/sec)			
Print Resolution	203 DPI			
Sensors	Cover Open, Paper End, Black Mark, Gap			
Battery (Standby)	41 Hours			
Battery (Printing)	3.5 Hours (30 second intervals)			
Buttons	Menu, Paper Feed, Menu Select, Power			

PAPER	
Type	Thermal Paper
Width	0.5" to 2" (12.7mm to 58mm)
Roll Diameter	Max 2.2" (56mm)
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page); International Characters 14
Character/Line	Font A (12 x 24) 32 columns Font B (9 x 17) 42 columns
Barcodes Supported	EAN-8, EAN-13, EAN-128, Postnet, Code39, Code93, Code128, Codabar, ITF, UPC-A, UPC-E, PDF417, QR Code, Maxicode, GS1 / DataBar™ (RSS) family, Datamatrix, Aztec

ACCESSORIES	
LK-POWER-CAR	Car Charging Cable
LK-P12-CRADLE1	Battery Charging Cradle for LK-P12 Battery
LK-P12-STRAP	Shoulder Strap for LK-P12
LK-P12-BATT-26	Spare 2600mAh Battery for LK-P12

PHYSICAL	
Dimension (WxDxH)	3.93" x 6.22" x 3.34" (100mm x 158mm x 85mm)
Weight (w/ Battery)	1.27 lbs (0.58kg)
Color	Black
Electrical	100–240 V 50/60 Hz (input) 8.55V / 1 Amp (output)
Drop Rating	5' (1.5m)
IP Rating	IP42

ENVIRONMENTAL	
Temperature	14°F to 131°F (-10°C to 122°C) operating -7.6°F to 140°F (-20°C to 60°C) storage
Humidity	10% to 90% non condensing
Warranty	1-year warranty
Certifications	FCC, UL, CE, Energy Star, RoHs
Operating System	Win 7, Win 8, Win 10, Win CE, Linux, Android, iOS