The LK-P22 receipt printer is a high end, feature rich mobile receipt printer. A 55 hour battery, high speed printing, and optional charging cradle make the LK-P22 the perfect enterprise grade mobile receipt printer. With support for all common command sets, the LK-P22 works with most software applications right out of the box.

COMPATIBILITY
Built in USB, Bluetooth or Wi-Fi, plus support for ESC/POS and ZPL commands, it's the perfect solution for any application

FAST PRINTING
Printing speeds of 4"/sec mean you're never left waiting for a receipt to print

EASY PAPER LOADING
Easy drop-in thermal paper loading won't slow you down on the go

LONG BATTERY LIFE
55 hours of standby and a quick 2 hour recharge time keep you powered up all day long

PART NUMBER	LK-P22-SB	LK-P22-SW
Interface Details	USB 2.0/Bluetooth 4.2	USB 2.0/Wi-Fi (802.11 a/b/g/n)
Emulation	ESC/POS, CPCL, ZPL Command compatible	
Print Method	Direct Thermal	
Printing Speed	4"/sec (100mm/sec)	
Print Resolution	203 DPI	
Sensors	Cover Open, Paper End, Black Mark	
Reliability	TPH Life 31 miles (50Km)	
Battery	1510mAh, 55Hrs stand-by	

PAPER

Type	Thermal Paper
Width	2.2" (58mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)
Roll Diameter	Max 1.57" (40mm)
Roll Core Inner Diameter	0.492" (12.5mm) ± 0.019" (0.5mm)
Character Set	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page); International Characters 14
Character/Line	Font A (12 x 24) 32 columns Font B (9 x 17) 42 columns
Barcodes Supported	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, UPC-E, PDF 417, QR CODE, DATAMATRIX, Aztec, RSS14, TLC39

ACCESSORIES

LK-POWER-CAR	Car Charging Cable
LK-P22-CRADLE1	Charging Cradle for LK-P22 (Requires LK-P2243-POWER)
LK-P2243-POWER	AC Power Adapter for LK-P22 and LK-P43 Cradle
LK-P2122-STRAP	Shoulder Strap for LK-P21 and LK-P22
LK-P22-BCLIP	Belt Clip for the LK-P22
LK-P22-CASE	Leather Case for the LK-P22
LK-P22-BATT-15	Spare 1510mAh Battery for LK-P22

PHYSICAL

Dimension (WxDxH)	3.15" x 4.69" x 1.73" (80mm x 119mm x 44mm)
Weight	0.53 lbs (242.5g)
Color	Black
Electrical	100 – 240 V 50/60 Hz (input) 8.55V / 1 Amp (output)
Drop Rating	5' (1.5m) on to concrete
Water and Dust Resistance	IP42, resistant to dripping water

ENVIRONMENTAL

Temperature	14°F to 122°F (-10°C to 50°C) operating -4°F to 140°F (-20°C to 60°C) storage
Humidity	35% to 80% non condensing
Warranty	1-year warranty
Certifications	FCC, UL, CE, Energy Star, RoHs
Operating System	Win 7, Win 8, Win 10, Win CE, Linux, Android, iOS

WARRANTY

ZWE-TMC	2 Year Warranty Extension
ZOE-TPC3	Next Business Day Protection
ZOE-TMC5	2 Year Warranty Extension + Next Business Day Protection
Certifications	FCC, UL, CE, Energy Star, RoHs
Operating System	Win 7, Win 8, Win 10, Win CE, Linux, Android, iOS