



### **Mobile Printers**

### 3" Mobile Receipt Printer

Featuring the patented Advanced Manual Cutter (AMC), the LK-P34 is the perfect mobile receipt printing solution. Featuring an industry standard 3" paper width and all common POS printing languages, the LK-P34 is sure to work right out of the box. With AMC technology one handed operation is a breeze, without the frustration of torn or ripped receipts.





#### **COMPATIBILITY**

Built in USB, Bluetooth or Wi-Fi, plus support for ESC/POS and ZPL commands, it's the perfect solution for any application.



#### **FAST PRINTING**

Printing speeds of 4"/sec mean you're never left waiting for a receipt to print.



#### **ADVANCED MANUAL CUTTER**

The manual cutter allows for easy one handed operation, and provides clean, professional receipts every time.



#### **LONG BATTERY LIFE**

Up to 77 hours of standby time keep you powered up all day long.









# Mobile Printers

# 3" Mobile Receipt Printer

PART NUMBER	LK-P34SB	LK-P34SW
Interface Details	USB 2.0/Bluetooth 4.2 + BLE	USB 2.0/Wi-Fi (802.11 a/b/g/n)
Emulation	ESC/POS, CPCL, ZPL Command compatible	
Character/Line	Font A (12 x 24), Font B (9 x 17)	
Barcodes Supported	1D: EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, UPC-E 2D: PDF 417, QR CODE, DATAMATRIX, Aztec, RSS14, TLC39	
Print Method	Direct Thermal	
Printing Speed	4"/sec (100mm/sec)	
Print Resolution		203 DPI
Sensors	Cover Open, Paper End, Black Mark	
Reliability	TPH Life 31 miles (50Km)	
Battery	2000mAh, 77Hrs stand-by	

PAPER	
Туре	Thermal Paper
Width	3.15" (80mm)
Thickness	0.002" (0.06mm) - 0.0035" (0.09mm)
Roll Diameter	1.69" (50mm) Maximum
Roll Core Inner Diameter	0.492" (12.5mm) Maximum

PHYSICAL	
Dimension (WxDxH)	4.25" x 5.7" x 2.2" (108mm x 145mm x 56mm)
Weight	0.91 lbs (415.3g)
Color	Black
Electrical	100-240 V 50/60 Hz (input) 8.4V / 800 - 1400 mA (output)
Water and Dust Resistance	IP54, resistant to splashing water and some dust

ENVIRONMENTAL	
Temperature	14°F to 122°F (-10°C to 50°C) operating -4°F to 140°F (-20°C to 60°C) storage
Humidity	10% to 80% non condensing
Warranty	1-year warranty
Certifications	FCC, UL, CE, Energy Star, RoHs
Operating System	Win 7, Win 8, Win 10, Win CE, Linux, Android, iOS

